

LS-85

E. A. Crosbie

August 18, 1986  
(No Distribution -  
For Reference Only)

**POSSIBLE LAYOUT FOR A 1.048 km CIRCUMFERENCE,  
THREE-MAGNET-PER-SECTOR, 7-GeV STORAGE RING**

(For cost comparison only)

E. A. Crosbie

Possible Layout for a 1.048 km Circumference, Three-Magnet  
per-Sector, 7 GeV Storage Ring  
(For cost comparison only)

The ring has 28 normal cells (32 m) with 6-meter insertion regions and 4 longer cells (38 m) with 12-meter insertion regions. It contains 3 quadrupoles at both ends of the insertion region and 8 quadrupoles in the dispersion region. The cell length parameters are shown in Table I. A possible set of lattice parameters are shown in Figs. 1 and 2.

This note is written for the purpose of cost comparison with the 800-m CDR ring. The final design of a lattice for this configuration may have a somewhat different circumference with different focusing element spacings and lengths. The magnet lengths ( 2 m) will probably remain unchanged.  
(B = 0.764 T at 7 GeV)

Table I

D = Drift      Q = Quadrupole      M = Bend Magnet      S = Sextupole

Bending radius of each magnet is  $\frac{2 \times 96}{2 \pi} = 30.558$  m.

Element	Length (M)	
M/2	1.0	
D	0.25	↑
S	0.50	
D	0.25	
Q	0.50	
D	0.50	
Q	0.50	6 m
D	0.25	
S	0.50	
D	0.25	
Q	0.50	
D	0.50	
Q	0.50	
D	0.25	
S	0.50	
D	0.25	↓
M	2.00	—
D	0.60	↑
Q	0.60	
D	0.60	7 m*
Q	1.00	
D	0.60	
Q	0.60	
D	3.00 <sup>†</sup>	↓

Reflect

\*10 m for long insertion cells

†6.00 m for long insertion cells

There are 28 32-m cells and 4 38-m cells. The circumference is 1048 m.



